

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE
REQUEST FOR FILING NATIONAL PATENT APPLICATION

Under 35 USC 111(a) and Rule 53(b)

PATENT APPLICATION

Hon. Commissioner of Patents
Washington, D.C. 20231

JC685 U.S. PTO



10/17/00

WITH SIGNED DECLARATION

NONPROVISIONAL
NON REISSUE
NON PCT NAT PHASE

JC685 U.S. PTO

09/686695



10/17/00

Sir:

Herewith is the PATENT APPLICATION of
Inventor(s): MATSUMOTO

Title SHUTTER FOR DIGITAL STILL CAMERAS

Atty. Dkt.: PM 274443
M#

SPO-2431
Client Ref

including:

Date: October 17, 2000

1. Specification: 29 pages (only spec. and claims) 2. ☐ Specification in non-English language
3. Declaration ☒ Original ☐ Facsimile/Copy ☒ Abstract 1 page(s); 4 numbered claims
4. ☒ Drawings: 5 sheet(s) ☐ informal; ☒ formal of size: ☒ A4 ☐ 11"
5. ☐ See top first page re prior Provisional, National or International application(s). ("X" box only if info is there and do not complete corresponding item 5 or 6). (Prior M# SN)
6. **AMEND the specification** please by inserting before the first line: -- This is a ☐ Continuation-in-Part
☐ Divisional ☐ Continuation ☐ Substitute Application (MPEP 201.09) of:
6(a) ☐ National Appln. No. / filed (M#)
6(b) ☐ International Appln. No. filed
7. ☐ **AMEND the specification** by inserting before the first line: -- This application claims the benefit of U.S.
Provisional Application No. 60/ , filed . --
8. ☒ Attached is an assignment and cover sheet. Please return the recorded assignment to the undersigned.
9. ☐ Prior application is assigned to

by Assignment recorded Reel Frame

10. **FOREIGN** priority is claimed under 35 USC 119(a)-(d)/365(b) based on filing in Japan

11. (country)

Application No.	Filing Date	Application No.	Filing Date
(1) 11-295701	October 18, 1999	(2)	
(3)		(4)	
(5)		(6)	
(7)		(8)	
(9)		<input type="checkbox"/> See 3 rd page for additional priorities	

12. (No.) Certified copy (copies): ☐ attached; ☐ previously filed (date)
in U.S. Application No. / filed on

13. Small entity status ☐ is **not** claimed; ☐ is claimed (**Pre-filing confirmation required**)

13(a). ☐ Attached: (No.) Small Entity Statement(s) (since 9/8/00 small entity statement(s) **not essential** to make claim)

14. **DOMESTIC/INTERNATIONAL** priority is claimed under 35 USC 119(e)/120/365(c) based on the following provisional, nonprovisional and/or PCT international application(s):

Application No.	Filing Date	Application No.	Filing Date
(1)		(4)	
(2)		(5)	
(3)		(6)	

15. ☐ This application is being filed under Rule 53(b)(2) since an inventor is named in the enclosed Declaration who was not named in the prior application.

16. ☐ Attached:

17. ☐ Preliminary Amendment:

THE FOLLOWING FILING FEE IS BASED ON CLAIMS AS FILED LESS ANY ABOVE CANCELLED

				Large/Small Entity		Fee Code
18. Basic Filing Fee				\$710/\$355	\$710	101/201
19. Total Effective Claims	6	minus 20 =	*0	x \$18/\$9 =	+ 0	103/203
20. Independent Claims	1	minus 3 =	*0	x \$80/\$40 =	+ 0	102/202
*If answer is zero or less, enter "0"						
21. If any proper multiple dependent claim (ignore improper) is present, add (Leave this line blank if this is a reissue application)				+ \$270/\$135	+ 270	104/204
22.	TOTAL FILING FEE ENCLOSED =				\$980	
23. If "non-English" box 2 is X'd, add Rule 17(k) processing fee				+ \$130	+ 0	139
24. If "assignment" box 8 is X'd, add recording fee				+ \$40	+ 40	581
25. <input type="checkbox"/> Attached is a Petition/Fee under Rule No.				+ \$130	+ 0	122
26.	TOTAL FEE ENCLOSED =				\$1020	

Our Deposit Account No. 03-3975

Our Order No. 61069 C# 274443 M#

CHARGE STATEMENT: The Commissioner is hereby authorized to charge any fee specifically authorized hereafter, or any missing or insufficient fee(s) filed, or asserted to be filed, or which should have been filed herewith or concerning any paper filed hereafter, and which may be required under Rules 16-18 (missing or insufficient fee only) now or hereafter relative to this application and the resulting Official document under Rule 20, or credit any overpayment, to our Account/Order Nos. shown above for which purpose a duplicate copy of this sheet is attached.

This CHARGE STATEMENT does not authorize charge of the issue fee until/unless an issue fee transmittal form is filed.

**Pillsbury Madison & Sutro LLP
Intellectual Property Group**

1100 New York Avenue, NW
Ninth Floor
Washington, DC 20005-3918
Tel: (202) 861-3000
GLK/ded

By Atty: G. Lloyd Knight

Reg. No. 17698

Sig: 

Fax: (202) 822-0944
Tel: (202) 861-3090

NOTE: File in duplicate with 2 post card receipts (PAT-103) & attachments

APPLICATION UNDER UNITED STATES PATENT LAWS

Atty. Dkt. No. PM 274443
(M#)

Invention: SHUTTER FOR DIGITAL STILL CAMERAS

Inventor (s): Junichi MATSUMOTO

Pillsbury Madison & Sutro LLP
Intellectual Property Group
1100 New York Avenue, NW
Ninth Floor
Washington, DC 20005-3918
Attorneys
Telephone: (202) 861-3000

This is a:

- ☐ Provisional Application
- ☒ Regular Utility Application
- ☐ Continuing Application
 - ☒ The contents of the parent are incorporated by reference
- ☐ PCT National Phase Application
- ☐ Design Application
- ☐ Reissue Application
- ☐ Plant Application
- ☐ Substitute Specification
 - Sub. Spec Filed _____
 - in App. No. _____ / _____
- ☐ Marked up Specification re
 - Sub. Spec. filed _____
 - In App. No _____ / _____

SPECIFICATION

SHUTTER FOR DIGITAL STILL CAMERA

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a motor-driven shutter for digital still cameras enabled to photograph by using a small-diameter aperture instead of a proper exposure aperture by the action of two relatively operating shutter blades.

2. Description of the Related Art

Generally, there are two kinds of lens shutters for digital still cameras, which are called "a normally closed shutter" and "a normally open shutter". Between these shutters, the normally open shutter is adapted so that when a power supply switch is closed, shutter blades are in a fully opened state, and an image of an object can be observed on the screen of a monitor, and that when the release button of the camera is depressed, photographing is started by supplying a photographing start signal to an image pickup device. Further, usually, the photographing is finished when an exposure aperture is closed by causing the shutter blades to perform a closing operation according to a photographing end signal, instead of supplying the photographing end signal to the image pickup device. Thereafter, upon completion of transfer of an imaging signal to a storage device during the closed state of the shutter blades, the shutter blades are reset to a fully opened state again. Thus, the camera gets ready for the next

photographing. Additionally, a sequence of such operations of the shutter blades is performed by a motor.

Meanwhile, among digital still cameras, there is known a camera having a diaphragm blade. In this case, there are two types of diaphragm mechanisms. One is adapted to have a plurality of diaphragm blades and enabled to continuously change the diameter of an exposure aperture. The other is adapted to selectively enter a preliminarily prepared aperture of a predetermined diameter into a proper exposure aperture. In either of the cameras respectively having the diaphragm mechanisms of these types, there are two manners of performing a diameter control operation. One is to start an exposure aperture control operation in a stage in which a power supply switch is closed. The other is to perform the exposure aperture control operation after the release button is depressed, and before photographing is started. Moreover, recently, in most of the cameras, a diaphragm mechanism is actuated by a motor.

Furthermore, there has been developed a motor for actuating the shutter blade and the diaphragm blade in this manner, which is previously called "an iris motor" and recently called "a moving magnet motor". This motor is configured so that an output pin (or driving pin) extending in parallel with a rotation shaft of a rotor constituted by a permanent magnet (usually, a two-pole permanent one) is integrally formed therewith in a radial position of the rotor, and that the rotor can be turned by an

angle within a predetermined range in a direction corresponding to a direction in which a current is supplied to a stator coil. Further, this motor can be manufactured at low cost and miniaturized still more and reduce power consumption, as
5 compared with a stepping motor.

Although a moving magnet motor is advantageous in cost reduction, miniaturization, and power consumption reduction over a stepping motor, it is disadvantageous for the cost reduction and miniaturization of the camera that a motor for
10 actuating the shutter blade is provided separately from a motor for actuating the diaphragm blade. Thus, preferably, it is sufficient for a camera to have only a single moving magnet motor. Moreover, desirably, the shutter blade is enabled to serve as the diaphragm blade, instead of providing the shutter blade and
15 the diaphragm blade separately from each other. Thus, there are expectations for the emergence of a shutter preferably configured so that two shutter blades relatively actuated by a single moving magnet motor serve as diaphragm blades, that the stopped state of the shutter blades is maintained at an exposure
20 aperture regulating position corresponding to a small-diameter exposure aperture instead of the proper exposure aperture at least during photographing since a moment just before the photographing is started, and that the shutter blades are closed from the exposure aperture regulating position when the
25 photographing is finished. The present invention relates to a

shutter for digital still cameras having such configuration.

Meanwhile, to actuate the shutter blades serving as the diaphragm blade by a single moving magnet motor, the shutter should be adapted so that the shutter blades are reliably stopped
5 at least at three positions, namely, a fully opened position, an exposure aperture regulating position, and a closed position. This is achieved, namely, these positions, at which the shutter blades are stopped, are reliably maintained by satisfying the following requirements. That is, among the three positions, at
10 the fully opened position, the stator coil of the motor is energized so that the shutter blades are operated in an opening direction in which these blades are opened. Further, at the closed position, the stator coil is energized so that the shutter blades are operated in a closing direction in which these blades
15 close. Moreover, at each of the three positions, the rotor or each of the shutter blades is made to abut against a stopper.

However, such a shutter has a drawback in that when the energization of the stator coil is once interrupted, the rotor can freely rotate and thus, the position of the rotor is not
20 determined. Therefore, to reliably maintaining the fully opened position and the closed position of the rotor even when the energization of the stator coil is interrupted, it is sufficient that a plurality of magnetic material members are arranged in such a manner as to face the peripheral surface of
25 each of the magnetic poles of the rotor, that an attractive force

acting between the magnetic material members due to the magnetic force of the rotor provides torque to the rotor, and that the stopper prevents the rotor from rotating. Further, in the case of the shutter configured in such a manner, it is sufficient to energize the stator coil only when the shutter blades are actuated. Thus, this shutter has an advantage in that the power consumption can be reduced.

Further, even in the case that the stopped state of the shutter blades can be maintained at the fully opened position and the closed position by configuring the shutter in such a manner, it is very difficult to reliably stop each of the shutter blades at the exposure aperture regulating position. That is, as described above, in the case of using this kind of the motor, when the energization of the stator coil thereof is interrupted, the stopped position of the rotor cannot be determined. Thus, it is considered that the stopped state of the rotor is maintained at the exposure aperture regulating position by energizing the stator coil thereby to provide torque to the rotor and by causing the spring member to prevent the rotor from rotating. However, in such a case, the energization of the stator coil should be continued so as to maintain the exposure aperture regulating position. Furthermore, when the shutter blades are closed from the exposure aperture regulating position, the shutter blades should be operated against the pushing force of the spring member. Thus, this requires a larger amount of electric power

than that required to turn the rotor from the fully opened position to the exposure aperture regulating position. Consequently, this shutter has a drawback in that the power consumption is increased.

- 5 Thus, it is considered as another method that the position of the rotor is regulated by sandwiching a driving pin, which is integrally formed with the rotor, between two spring members respectively having pushing forces that act in different directions, or between both end portions of a torsion spring.
- 10 However, in such a case, the rotor should be operated against the pushing force of each sprig both when the shutter blades are caused to perform the opening operation, and when the shutter blades are caused to perform the closing operation. Therefore, the power consumption of the shutter is not sufficiently reduced
- 15 on the whole. Furthermore, in such a case, it is difficult to manufacture the shutter so that the rotor reliably stands still at the predetermined position. Even in the case that the shutter can be manufactured so that the rotor can stand still at the predetermined position, the rotor cannot be reliably held at the
- 20 predetermined position owing to the fitting tolerance of a connecting portion between the driving pin of the rotor and the shutter blade.

SUMMARY OF THE INVENTION

Accordingly, an object of the present invention is to

provide a shutter for digital still cameras, which is suitable for reducing the cost, size and power consumption, and which has a single motor of the type being capable of determining the direction of rotation of the rotor thereof according to a direction of flow of electric current supplied to a stator coil uses a driving pin integrally provided with the rotor to thereby cause two relatively operating shutter blades to perform opening and closing operations and is enabled by an extremely simple configuration to maintain the stopped state of each shutter blade at the three positions, namely, the fully opened position, the exposure aperture regulating position, and the closed position even when a stator coil is not energized.

To achieve the foregoing object, according to an aspect of the present invention, there is provided a shutter for digital still cameras, which comprises a motor having a rotor constituted by a two-pole permanent magnet integrally provided with a driving pin at a radial position thereof in such a manner as to extent in parallel with a rotation shaft thereof that reciprocatingly moves by a predetermined rotational angle from an initial position correspondingly to a direction, in which electric current is supplied to a stator coil, two shutter blades being operative to relatively operate together with the driving pin and to perform operations of opening and closing the exposure aperture, a plurality of magnetic holding means, disposed separately from one another in such a way as to face a peripheral

surface of each magnetic pole of the rotor, and configured so that an attractive force caused from a magnetic force of the rotor acting between the rotor and each of the plurality of magnetic holding means is exerted in one of directions of rotation of the rotor in a corresponding one of angular regions, the border between which corresponds to a midpoint angular position in the rotational angle, and pushing means for maintaining a small-diameter exposure aperture regulating state, which is caused by the two shutter blades, in cooperation with the attractive force by directly or indirectly preventing rotation of the rotor when energization of the coil is interrupted at a diameter regulating position at which the rotor rotates beyond the midpoint angular position by a predetermined angle.

Further, in the case of an embodiment of the shutter for digital still cameras according to the present invention, the pushing means is adapted so that the pushing force thereof, which acts in such a manner as to cause the rotor and the two shutter blades to operate to the midpoint angular position, does not act at all or hardly acts at a position where the rotor stops after the rotor rotates beyond the exposure aperture regulating position in a direction opposite to the midpoint angular position. Thus, the stopped position, at which the rotor stops, in the closed state, in which the exposure aperture is closed, can be more reliably held.

Moreover, in the case of an embodiment of such a shutter

for digital still cameras according to the present invention,
the pushing means is one or two torsion springs and adapted to
be directly in contact with the two shutter blades. Thus,
backlash due to the fitting tolerance between the driving pin
5 of the rotor and the shutter blade is eliminated. Consequently,
the shape of the small-diameter exposure aperture formed by the
shutter blades can stably be obtained.

Furthermore, in the case of an embodiment of the shutter
for a digital still camera according to the present invention,
10 the pushing means is a torsion spring wound around the shaft
outside a blade chamber. The small-diameter exposure aperture
regulating state, which is caused by the two shutter blades, is
maintained in a state in which both end portions of the torsion
spring face an operating locus of each of the two shutter blades
15 in the blade chamber and are engaged with at least one of two
base plates of the blade chamber. Thus, the configuration of
the shutter is simplified. Consequently, a low-cost shutter is
obtained.

BRIEF DESCRIPTION OF THE DRAWINGS

20 Other features, objects and advantages of the present
invention will become apparent from the following description
of a preferred embodiment with reference to the drawings in which
like reference characters designate like or corresponding parts
throughout several views, and in which:

FIG. 1 is a plan view of an embodiment of the present invention, which is incorporated into a camera, when viewed from an image-pickup-device side;

FIG. 2 is a rear view of the embodiment illustrated in FIG. 1;

FIG. 3 is a sectional view of the embodiment for understanding the overlapping relation among constituent members of the embodiment;

FIG. 4 is a plan view of the embodiment in the case of using a small-diameter exposure aperture; and

FIG. 5 is a plan view of the embodiment, which illustrates the closed state of shutter blades.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Hereinafter, an embodiment of the present invention will be described in detail by referring to FIGS. 1 to 5. This embodiment is a normally open shutter to which the present invention is applied. First, the configuration of this shutter is described hereinbelow by referring to FIGS. 1 to 3. A shutter base plate 1 is made of a synthetic resin. A blade chamber is formed between the shutter base plate 1 and an auxiliary base plate 2. Both the base plates 1 and 2 are attached to each other by screws 3 and 4. Further, circular apertures 1a and 2a are formed in the central portions of the shutter base plate 1 and the auxiliary base plate 2, respectively. An exposure aperture

is formed by concentrically arranging these apertures 1a and 2a. Furthermore, two sets of circular holes 1b and 2b, and 1c and 2c are formed so that the circular holes of each of the sets are respectively formed in the shutter base plate 1 and the auxiliary
5 base plate 2 and concentrically arranged.

A moving magnet motor is mounted on the top surface side, that is, the pickup-device-side of the shutter base plate 1. A rotor 5 is constituted by a two-pole permanent magnet magnetized in a radial direction. In this embodiment, each of a rotation
10 shaft 5a and a driving pin 5b is made of a synthetic resin. Further, each of the rotation shaft 5 and the driving pin 5b, which is formed at a position in a radial direction of the rotation shaft 5a in such a way as to extend in parallel with the shaft 5a, is made of a synthetic resin and integrally outsert-molded
15 with each other. Furthermore, the two magnetic poles are separated by a line passing through the rotation shaft 5a and the driving pin 5b. Moreover, a stator frame consists of an upper frame 6 and a lower frame 7, each of which is made of a synthetic resin. Both ends of the rotation shaft 5a are bearing-supported
20 by these frames that are attached to each other through a plurality of hook portions 6a (only one of which is shown in FIG. 3) of the upper frame 6. Furthermore, an elongated hole 7a is formed in the lower frame 7. The driving pin 5b penetrates through the elongated hole 7a. Additionally, the driving pin
25 5b penetrates through an elongated hole 1d formed in the shutter

base plate 1 and an elongated hole 2d formed in the auxiliary base plate 2. Further, a coil 8 is wound therearound in such a manner as to cover the bearing-support portions of the upper frame 6 and the lower frame 7.

5 Moreover, the upper frame 6 is cylindrically formed, and a cylindrical yoke 9 is fitted into an outer peripheral portion thereof. Furthermore, as illustrated in FIG. 1, four iron pins 10, 11, 12 and 13 (hereunder sometimes referred to generically as "holding means") are press-fitted into groove holes 6b, 6c,
10 6d, 6e formed in the upper frame 6, respectively. Further, the iron pins 10 and 11 are placed at positions, which are symmetrical to the positions of the iron pins 12 and 13 with respect to a horizontal line passing through the rotation shaft 5a. Furthermore, the motor constructed in this way is attached to
15 the shutter base plate 1 with two screws 14 and 15.

Next, the configuration of the rear side of the shutter base plate 1 is described hereinbelow. Three shafts 1e, 1f, and 1g and two stoppers 1h and 1i are formed on the shutter base plate 1 in such a way as to be integral with one another. Among these
20 shafts and stoppers, the end portions of the shafts 1e and 1f and the stopper 1h are fitted into the holes formed in the auxiliary base plate 2. Further, the shaft 1g penetrates through the hole formed in the auxiliary base plate 2 and largely protrudes from the rear side thereof. A spring 16 is wound around
25 such a projection. The spring 16 has bent portions 16a and 16b

respectively formed at both ends thereof. As shown in FIGS. 1 and 2, the bent portion 16a is engaged with the holes 1c and 2c, while the bent portion 16b is engaged with the holes 1b and 2b. As will be described in the following description, these bent portions 16a and 16b face inside the operating locus of each of the shutter blades, and are moved in the holes by the operations of the shutter blades.

A pair of shutter blades 17 and 18 is rotatably connected to each of the shafts 1e and 1f. The driving pin 5b is fitted into elongated holes 17a and 18a of the shutter blades 17 and 18. Thus, when the rotor 5 is turned counterclockwise as viewed in FIG. 1, the shutter blades 17 and 18 perform a closing operation. Thereafter, when the rotor 5 rotates clockwise, the shutter blades 17 and 18 perform an opening operation. Further, each of these shutter blades 17 and 18, which are of the same shape, has a corresponding one of diameter regulating portions 17b and 18b for regulating a small-diameter apertures, a corresponding one of pushing means 17c and 18c for stretching the spring 16, and a corresponding one of engaging portions 17d and 18d for maintaining the stretched state of the spring 16.

Next, an operation of this embodiment is described hereinbelow. The shutter blades do not cover the entire surface of the image pickup device except when the shutter is in a state caused just upon completion of photographing. Further, FIGS. 1 and 2 illustrate a state in which the camera is not used, that

is, a power supply switch is not closed. Thus, in this state, naturally, a coil 8 is not energized. However, this embodiment is enabled to reliably maintain the rotational position of the rotor 5 by the action of a magnetic force of the rotor 5.

5 That is, in this state, the magnitude of an attractive force acting between the N-pole of the rotor 5 and the iron pin 11 is larger than that of an attractive force acting between the N-pole of the rotor 5 and the iron pin 10. Further, the magnitude of an attractive force acting between the S-pole of the rotor 5 and
10 the iron pin 12 is larger than that of an attractive force acting between the S-pole of the rotor 5 and the iron pin 13. Thus, a force for turning the rotor 5 clockwise is provided to the rotor 5. Furthermore, the driving pin 5b pushes the shutter blades 17 and 18 in an opening direction in which the exposure aperture
15 is opened. However, the stopper 1h prevents the shutter blade 18 from operating, so that this state is maintained.

Incidentally, such a state is sometimes maintained under some conditions even when the iron pins 10 and 12 are omitted or the iron pins 11 and 13 are omitted. However, in consideration of
20 reliability, this embodiment has all of such iron pins.

When the shutter is in the state illustrated in FIGS. 1 and 2, the power supply switch is first closed. Among cameras each having a monitor, there is known a camera enabled to automatically set a diaphragm aperture, which meets depth-
25 of-field requirements, by the action of a photometer or a range

finder when a power supply switch is closed, even in the case that a release button is not depressed. The present invention can be applied to a camera of such a type. However, the following description describes the case of using the shutter of the present invention in a camera of the type, in which the diaphragm aperture is not automatically set only by closing the power supply switch. Therefore, in the case of this embodiment, the coil 8 is not energized even when the power supply switch is closed. Consequently, the state illustrated in FIGS. 1 and 2 are maintained as it is.

Thus, first, an operation of this embodiment in the case of selecting a small-diameter exposure aperture at the time of photographing is described hereinbelow. When a release button is depressed so as to take a picture, the energization of the coil 8 is started in such a manner as to supply electric current thereto in a forward direction, and the rotor 5 is rotated counterclockwise against a holding force acting between the rotor 5 and the holding means (or iron pins). Further, needless to say, this holding force weakens as the rotor 5 rotates. Furthermore, as the rotor 5 rotates, the rotor 5 causes the shutter blades 17 and 18 by using the driving pin 5b to relatively operate, so that the aperture 1a is closed.

Then, the rotor 5 reaches a midpoint angular position in the rotational angle by which the rotor 5 can rotate. That is, the rotor 5 reaches a position just before the position

illustrated in FIG. 4. Further, at the midpoint angular position, the border between the N-pole region and the S-pole region is in a horizontal position illustrated in FIG. 4. Thus, the positions of the iron pins 10 and 11 are symmetrical to those of the iron pins 12 and 13 with respect to the border. Therefore, in the case that the energization of the coil 8 for supplying a current thereto in a forward direction is interrupted when the rotor 5 reaches the midpoint angular position, theoretically, the rotor 5 stops at the midpoint angular position, and this stopped state of the rotor 5 is maintained, on condition that the inertial forces of the rotor 5 and the shutter blades 17 and 18 are not take into consideration.

However, it is very difficult to achieve the stopped state at the midpoint angular position in this way. In the case that the rotor 5 does not stop at the midpoint angular position but the actually stopped position of the rotor 5 is a little deviated from the midpoint angular position, the balance among the holding forces acting among the holding means is lost, so that the rotor 5 rotates in one of the rotational directions. Therefore, to stop the rotor 5 at the midpoint angular position even when the balance among the holding forces is lost, the rotation of the rotor 5 should be regulated by two position regulating members. However, even in such a case, there is a problem that a small-diameter exposure aperture regulating state, in which the diameter of the small-diameter exposure aperture is regulated

by the shutter blades 17 and 18, is extremely unstable owing to the presence of the fitting tolerance between the driving pin 5b and each of the elongated holes 17a and 18a of the shutter blades 17 and 18.

Thus, this embodiment is adapted so that the rotor 5 is reliably stopped at a position slightly deviated in a counterclockwise direction from the midpoint angular position, instead of being stopped at the midpoint angular position, and that a small-diameter exposure aperture is stably obtained.

That is, in the state illustrated in FIG. 4, the magnitude of an attractive force acting between the N-pole of the rotor 5 and the iron pin 10 is slightly larger than that of an attractive force acting between the N-pole of the rotor 5 and the iron pin 11. Further, the magnitude of an attractive force acting between the S-pole of the rotor 5 and the iron pin 13 is slightly larger than that of an attractive force acting between the S-pole of the rotor 5 and the iron pin 12. Consequently, a force for causing the rotor 5 to rotate counterclockwise is exerted on the rotor 5. Therefore, the shutter blades 17 and 18 are pushed in a closing direction, in which these blades are closed, by the driving pin 5b.

Further, the pushing portions 17c and 18c of the shutter blades 17 and 18 are in contact with the bent portions 16a and 16b of the spring 16. However, the magnitude of the pushing force of the spring 16 is larger than that of the force causing the

shutter blades 17 and 18 to close. Thus, this state illustrated in FIG. 4 is maintained during the non-energization state of the coil. Furthermore, the driving pin 5b and the spring 16 push the shutter blades 17 and 18 in opposite directions. Thus, the problem due to the fitting tolerance between the driving pin 5b and each of the elongated holes 17a and 18a does not occur. Consequently, the exposure aperture regulating portions 17b and 18b appropriately maintain the small-diameter exposure aperture.

The small-diameter exposure aperture is formed in this way. Subsequently, a photographing start signal is supplied to the image pickup device. Further, when a predetermined photographing time elapses, a control circuit issues a closing signal for closing the shutter blades 17 and 18. In response to this signal, the energization of the coil 8 is started again in such a manner as to supply a current in a forward direction thereto. Thus, the rotor 5 is rotated counterclockwise still more from the position illustrated in FIG. 4. The aperture 1a is closed by the shutter blades 17 and 18, as illustrated in FIG. 5. Then, the photographing is finished. The rotation of the rotor 5 is stopped by causing an end portion of the shutter blade 17 to abut against the stopper 1i. Incidentally, when the shutter blades 17 and 18 are closed from the position illustrated in FIG. 4, these shutter blades are moved against the pushing force of the spring 16. Thus, the closing operation is

preferably achieved by setting the current value of electric current, which is supplied to the coil 8 at that time, (or by setting the voltage value) to larger than that supplied in the case that the closing operation is performed until the rotor 5 is rotated to the exposure aperture regulating position.

Although the present invention inhibits the coil 8 from being energized in the state illustrated in FIG. 5 in such a way as to supply electric current in a forward direction thereto, the energization of the coil 8 for supplying electric current thereto in a forward direction is interrupted in this embodiment for the purpose of saving the power consumption, so that the Coil 8 is put into a non-energized state. Further, even in such case, the state illustrated in FIG. 5 is reliably maintained for the following reason. That is, in this state, the magnitude of an attractive force acting between the N-pole of the rotor 5 and the iron pin 10 is larger than an attractive force acting between the N-pole of the rotor 5 and the iron pin 11. Moreover, the magnitude of an attractive force acting between the S-pole of the rotor 5 and the iron pin 13 is larger than an attractive force acting between the S-pole of the rotor 5 and the iron pin 12. Thus, a force causing the rotor 5 to rotate counterclockwise is provided thereto. On the other hand, the bent portions 16a and 16b of the spring 16 are in contact with the engaging portions 17d and 18d, which are formed like arcs respectively centered on the shafts 1e and 1f, of the shutter blades 17 and 18. Thus,

the pushing force for pushing the shutter blades 17 and 18 in a direction, in which these blades open, does not act at all. Even when slightly acts thereon, the magnitude of such a force is far smaller than that of the force caused by the holding means.

5 Incidentally, as is understood from this, in the case of this embodiment, the timing, with which the energizing of the coil 8 is interrupted, can be set so that the energization thereof is interrupted before the shutter blades 17 and 18 close the aperture 1a and stop. That is, unless the magnitude of a
10 resultant force of the force, which is caused due to the presence of the holding means in such a way as to rotate the rotor 5 counterclockwise, and the inertial forces of the shutter blades 17 and 18 is smaller than the force of the spring 16, which causes the rotor 5 to rotate clockwise, the shutter blades 17 and 18
15 continue to perform the closing operation until each of these blades reach the closed position illustrated in FIG. 5. However, preferably, the closing operation is achieved as quickly as possible. Thus, it is not preferable that the energization of the coil is interrupted well before these blades 17 and 18 close
20 the aperture 1a.

When data representing a result of the photographing is stored in a storage device after the aperture 1a is closed in this manner, the shutter blades 17 and 18 are caused to perform the opening operation. In this case, conversely to the
25 aforementioned case, the energization of the coil 8 is performed

in such a manner as to supply electric current in a reverse direction. Therefore, a force causing the rotor 5 to rotate clockwise is provided thereto. Thus, the rotor 5 is rotated clockwise against the holding force of the holding means, which causes these blades to move to the closed position. After passing through the position illustrated in FIG. 4, the rotor 5 is stopped by causing the shutter blade 18 to abut against the stopper 1h. Further, the larger the current value of electric current (or the voltage value of a voltage) supplied to the coil 8 becomes, the more quickly the opening operation of the shutter blades 17 and 18 is achieved at that time. Further, subsequently, the energization of the coil 8 is interrupted, so that the shutter is reset to the state illustrated in FIGS. 1 and 2. This state is maintained until the next photographing is performed in the aforementioned manner.

Incidentally, needless to say, even when the energization of the coil 8 is interrupted after the rotor 5 rotates beyond the midpoint angular position halfway through the opening operation, the rotor 5 is returned to the state illustrated in FIG. 1 by the action of the attractive force acting between the rotor 5 and the holding means. Further, in the case where the shutter is set in this embodiment so that the photographing is successively performed, and in the case that the small-diameter exposure aperture is automatically set when the power supply switch is closed, differently from the case of this embodiment,

the rotor is stopped at the position illustrated in FIG. 4 and the shutter gets ready for the next photographing at this position when the energization of the coil 8 is interrupted at the time, at which the rotor 5 reaches close to the position
5 illustrated in FIG. 4 in the course of the resetting operation.

Next, the case of photographing by using the large-diameter exposure aperture 1a, namely, the exposure aperture without selecting the small-diameter exposure aperture in the aforementioned manner is described hereinbelow. Incidentally,
10 parts of the following description, which may overlap with the foregoing description of the case of selecting the small-diameter aperture, are omitted or simplified. First, when a release button is depressed so as to take a picture, a photographing start signal is immediately supplied to the image
15 pickup device, such as CCD, in this case. Then, after a lapse of a predetermined photographing time, the control circuit issues a closing signal to each of the shutter blades 17 and 18. Thus, the energization of the coil 8 is started in such a manner as to supply electric current thereto in a forward
20 direction, and thus the rotor 5 is rotated counterclockwise from the position illustrated in FIG. 1.

Consequently, the shutter blades 17 and 18 are relatively actuated by the driving pin 5b to thereby close the aperture 1a. However, even when the blades 17 and 18 reach the position
25 illustrated in FIG. 4, these shutter blades do not stop. The

pushing portions 17c and 18c push the bent portions 16a and 16b. Thus, the same operation is continued. Then, even in the case that the energization of the coil 8 is interrupted when these blades reach the position illustrated in FIG. 5, the rotor 5 is not rotated clockwise by the pushing force of the spring 16. That is, this state is maintained. Further, as described above, the timing, with which the energization of the coil 8 is interrupting, may be set so that the energization thereof is interrupted immediately before the shutter blade 17 abuts against the stopper 11. Then, after the shutter blades 17 and 18 close the aperture 1a, data representing a result of the photographing is stored in the storage device. Subsequently, the shutter is reset. Such an operation performed in this case is substantially the same as that in the case of selecting the small-diameter exposure aperture.

Meanwhile, even in the case that a relatively large number of holding means are provided in the shutter like this embodiment, and that the fully open state and the closed state of the aperture 1a are thus reliably maintained, this is achieved by utilizing only the magnetic force of the rotor 5. Thus, it is not ensured that the positions of the shutter blades 17 and 18, namely, the rotational position of the rotor 5 are normal positions illustrated in FIGS. 1 and 5 at the moment at which the energization of the coil 8, which has been in the non-energized state, is started. Moreover, because a time period, in which

the shutter is in the state illustrated in FIG. 5, is very short, there is almost no likelihood that the shutter blades 17 and 18, and the rotor 5 are not in the normal positions. Even when such an unfavorable situation occurs, the shutter is then reset to the state illustrated in FIG. 1. Consequently, there is no problems in particular. However, when such an unfavorable situation occurs during the shutter is in the state illustrated in FIG. 1, there is a fear that a serious problem occurs.

Thus, now consider the case that such an unfavorable situation occurs when the small-diameter exposure aperture is selected. It is preliminarily determined according to design specifications how long a forward current for energization is supplied to the coil 8 so as to rotate the rotor 5, which has been in the position illustrated in FIG. 1, and as to then stop the rotor 5 in the position illustrated in FIG. 4. Therefore, in the case that the rotor 5 is rotated counterclockwise from the position illustrated in FIG. 1 when the energization of the coil 8 is started in such a way as to supply a current in a forward direction, the rotor 5 is rotated counterclockwise by a considerable amount from the position illustrated in FIG. 4. Thus, the bent portions 16a and 16b of the spring 16 may be in contact with the engaging portions 17d and 18d of the shutter blades 17 and 18. Further, when the energization of the coil 8 is interrupted, the magnitude of the force acting between this spring and the holding means in such a way as to attract and return

the blades to the closed position is larger than the pushing force of the spring 16, the rotor 5 does not return to the position illustrated in FIG. 4 but is rotated to the position thereof illustrated in FIG. 5. That is, the shutter is brought into a state to be caused just upon completion of photographing.

Thus, to prevent an occurrence of such a phenomenon, although the set-up of the shutter is a little time-consuming, it is sufficient that the energization of the coil 8 in such a manner as to supply a current thereto in a reverse direction is performed for a predetermined time before the energization of the coil 8 having been in the state illustrated in FIG. 1 is performed in such a manner as to supply a current thereto in a forward direction, and that therefore, the energization of the coil 8 for supplying a current thereto in a forward direction is performed after the rotor 5 is pushed in such a way as to rotate clockwise by once performing the energization of the coil 8 for a predetermined time in such a manner as to supply a current thereto in a reverse direction. Furthermore, in the case of photographing by using a large-diameter exposure aperture, a similar phenomenon presents a serious problem. In such a case, it is sufficient that the energization of the coil 8 for supplying a current thereto in a reverse direction is once performed before a photographing start signal is provided to the image pickup device.

Incidentally, the aforementioned embodiment is adapted so

that the energization of the coil 8 for supplying a current in a forward direction is interrupted in a state in which the shutter blades 17 and 18 are closed. However, the present invention is applicable to the case that the energization of the coil 8 for supplying a current thereto in a forward direction is continued until the energization thereof for supplying a current thereto in a reverse direction is performed. Further, although the aforementioned embodiment is adapted so that the single spring 16 can push the shutter blades 17 and 18, this single spring 16 may be replaced with two separate springs. Moreover, this spring 16 may be wound around the shaft 1g in the blade chamber. Furthermore, although the aforementioned embodiment is adapted so that the spring 16 can directly push the shutter blades 17 and 18, these shutter blades may be pushed by this spring through another constituent member. Additionally, the present invention does not inhibit the shutter from being adapted so that the spring 16 directly pushes the rotor 5. However, according to the embodiment, the configuration of the entire shutter is simplified. Moreover, the assembling of the shutter is facilitated. Furthermore, the predetermined functions can reliably be realized.

As described above, according to the present invention, there is provided a shutter for a digital camera, in which a single moving magnet motor having a permanent magnet rotor adapted to reciprocatingly rotate within a predetermined rotation angle

range according to a direction of flow of electric current supplied to a stator coil uses a driving pin integrally provided with the rotor to thereby cause two relatively operating shutter blades to perform opening and closing operations. Moreover, the

- 5 shutter of the present invention is enabled by an extremely simple configuration to accurately stop each shutter blade at the three positions, namely, the fully opened position, the exposure aperture regulating position, and to preferably maintain the stopped state of each of the shutter blades. Thus,
- 10 the shutter of the present invention is extremely advantageous in cost reduction and miniaturization of a shutter for digital still cameras. Moreover, the shutter of the present invention can reliably maintain the stopped state of the rotor at all the three positions without energizing the stator coil.
- 15 Consequently, the shutter of the present invention is extremely advantageous in saving the power consumption of a shutter.

- Although the preferred embodiment of the present invention have been described above, it should be understood that the present invention is not limited thereto and that other
- 20 modifications will be apparent to those skilled in the art without departing from the spirit of the invention.

The scope of the present invention, therefore, should be determined solely by the appended claims.

WHAT IS CLAIMED IS:

1. A shutter for digital still cameras, comprising:

a motor having a stator including an energizing coil,
having a rotor constituted by a two-pole permanent magnet and
capable of reciprocatingly moving by a predetermined rotational
5 angle correspondingly to a direction in which a current is
supplied to said coil, and having a driving pin integrally
provided with said rotor and extending in parallel with a
rotation shaft of said rotor;

two shutter blades capable of being relatively moved by
10 said driving pin to open and close an exposure aperture;

a plurality of magnetic holding means respectively disposed
against each magnetic pole of said rotor, and configured so that
an attractive force caused from a magnetic force of said rotor
acting between said rotor and each of said plurality of magnetic
15 holding means is exerted to rotate said rotor in either direction
from a midpoint angular position in the rotational angle; and

forcing means capable of directly or indirectly preventing
rotation of said rotor, and maintaining a small-diameter
exposure aperture regulating state by said two shutter blades
20 in cooperation with the attractive force, when energization of
said coil is interrupted at an exposure aperture regulating
position at which said rotor rotates beyond the midpoint angular
position by a predetermined angle.

2. A shutter for digital still cameras according to claim 1,
wherein the urging force of said forcing means which acts so as
to cause said rotor and said two shutter blades to operate to
the midpoint angular position, does not act at all or hardly acts
5 at a position where said rotor stops after said rotor rotates
beyond the exposure aperture regulating position in a direction
opposite to the midpoint angular position.

3. A shutter for digital still cameras according to claim 1 or
2, wherein said forcing means is one or two torsion springs and
adapted to be directly in contact with said two shutter blades.

4. A shutter for digital still cameras according to claim 1 or
2, wherein said forcing means is a torsion spring wound around
said shaft outside a blade chamber, and wherein the small-
diameter aperture regulating state, which is caused by said two
5 shutter blades, is maintained in a state in which both end
portions of said torsion spring are positioned respectively on
an operating locus of each of said two shutter blades in said
blade chamber and are engaged with at least one of two base plates
of said blade chamber.

ABSTRACT OF THE DISCLOSURE

A rotor is constituted by a two-pole permanent magnet, and enabled to rotate by a predetermined angle in a direction corresponding to the direction of electric current supplied to a stator coil. Two shutter blades are moved by a driving pin which is integrally provided with the rotor, to perform opening and closing operations. A fully opened state and a closed state, which are obtained by such operations, are maintained by an attractive force, which is obtained from a magnetic force of the rotor and acts between the rotor and each of four iron pins, even when the stator coil is not energized. Further, an exposure aperture regulating position established by a closing operation of the two shutter blades is beyond a midpoint position corresponding to an intermediate state from the fully opened state to the closed state. Moreover, an exposure aperture regulating state is maintained by the attractive force, which acts during a non-energized state of the stator coil so as to cause the shutter blades to close, and the urging force of a spring.

FIG.1




FIG.2




FIG. 3






FIG.4



	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2423	2424	2425	2426	2427	2428	2429	2430	2431	2432	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---



FOR UTILITY/DESIGN
CIP/PCT NATIONAL/PLANT
ORIGINAL/SUBSTITUTE/SUPPLEMENTAL
DECLARATIONS

RULE 63 (37 C.F.R. 1.63)
DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATION
IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

PM & S
FORM

As a below named inventor, I hereby declare that my residence, post office address and citizenship are as stated below next to my name, and I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the INVENTION ENTITLED

SHUTTER FOR DIGITAL STILL CAMERAS

the specification of which (CHECK applicable BOX(ES))

X A. ☒ is attached hereto.
BOX(ES) → B. ☐ was filed on _____ as U.S. Application No. _____ /
→ C. ☐ was filed as PCT International Application No. PCT/ _____ / _____ on _____

and (if applicable to U.S. or PCT application) was amended on _____

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose all information known to me to be material to patentability as defined in 37 C.F.R. 1.56. Except as noted below, I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International Application which designated at least one other country than the United States, listed below and have also identified below any foreign application for patent or inventor's certificate, or PCT International Application, filed by me or my assignee disclosing the subject matter claimed in this application and having a filing date (1) before that of the application on which priority is claimed, or (2) if no priority claimed, before the filing date of this application:

PRIOR FOREIGN APPLICATION(S)

Number Country Day/MONTH/Year Filed Date first Laid-open or Published Date Patented or Granted Priority NOT Claimed

Hei 11-295701 Japan 18/October/1999

If more prior foreign applications, X box at bottom and continue on attached page.

Except as noted below, I hereby claim domestic priority benefit under 35 U.S.C. 119(e) or 120 and/or 365(c) of the indicated United States applications listed below and PCT international applications listed above or below and, if this is a continuation-in-part (CIP) application, insofar as the subject matter disclosed and claimed in this application is in addition to that disclosed in such prior applications, I acknowledge the duty to disclose all information known to me to be material to patentability as defined in 37 C.F.R. 1.56 which became available between the filing date of each such prior application and the national or PCT international filing date of this application:

PRIOR U.S. PROVISIONAL, NONPROVISIONAL AND/OR PCT APPLICATION(S)

Application No. (series code/serial no.) Day/MONTH/Year Filed Status Priority NOT Claimed
pending, abandoned, patented

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

And I hereby appoint Pillsbury Madison & Sutro LLP, Intellectual Property Group, 1100 New York Avenue, N.W., Ninth Floor, East Tower, Washington, D.C. 20005-3918, telephone number (202) 861-3000 (to whom all communications are to be directed), and the below-named persons (of the same address) individually and collectively my attorneys to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith and with the resulting patent, and I hereby authorize them to delete names/numbers below of persons no longer with their firm and to act and rely on instructions from and communicate directly with the person/assignee/attorney/firm/ organization who/which first sends/sent this case to them and by whom/which I hereby declare that I have consented after full disclosure to be represented unless/until I instruct the above firm and/or a below attorney in writing to the contrary.

Paul N. Kokulis	16773	Paul E. White, Jr.	32011	Stephen C. Glazier	31361	Adam R. Hess	41835
Raymond F. Lippitt	17519	Glenn J. Perry	28458	Ruth N. Morduch	31044	William P. Atkins	38821
G. Lloyd Knight	17698	Kendrew H. Colton	30368	Richard H. Zaitlen	27248	Paul L. Sharer	36004
Kevin E. Joyce	20508	G. Paul Edgell	24238	Roger R. Wise	31204		
George M. Sirilla	18221	Lynn E. Eccleston	35861	Jay M. Finkelstein	24802		
Donald J. Bird	25323	Timothy J. Klima	34852	Michael R. Dzwonczyk	36787		
Peter W. Gowdey	25872	David A. Jakopin	32995	W. Patrick Bengtsson	32456		
Dale S. Lazar	28872	Mark G. Paulson	30793	Jack S. Barufka	37087		

(1) INVENTOR'S SIGNATURE:

Junichi Matsumoto

Date:

October 2, 2000

Junichi		MATSUMOTO	
First	Middle Initial	Family Name	
Residence	Warabi-shi	Saitama	Japan
City	State/Foreign Country		Country of Citizenship
Post Office Address	c/o NIDEC COPAL CORPORATION, 18-10, Shimura 2-chome, Itabashi-ku,		
(include Zip Code)	Tokyo 174-8550, Japan		

(2) INVENTOR'S SIGNATURE:

Date:

First	Middle Initial	Family Name	
Residence			
City	State/Foreign Country		Country of Citizenship
Post Office Address			
(include Zip Code)			

FOR ADDITIONAL INVENTORS, "X" box ☐ and proceed on the attached page to list each additional inventor.
☐ See additional foreign priorities on attached page (incorporated herein by reference).

Atty. Dkt. No. PM

(M#)